



WA Applications for Steel Industry





Why work with Welding Alloys Group?

WA Group specialises in refurbishing and fabrication of these components:

- Continuous Casting Rolls / Furnace Rolls
- Work Rolls / Back-up Rolls
- Run-out Table Rolls
- Pinch/Wrapper Rolls

- Galvanizing Pots
- Sintering
- Forming Rolls
- Mandrels

Welding Alloys Group provides complete, innovative and customised surface protection solutions to the iron and steel manufacturing industry.

- The largest range
 of wear resistant cored wires :
 Chromecore, Hardface, Stelloy
- Automated welding equipment for surfacing, joining and cladding : Roll Cladder, MultiSurfacer™
- Engineered wear protection solutions INTEGRA : 3D-*Carb* Technology, Hard*plat*e™







Our brands specialised in wear protection solutions:



Wholly owned subsidiary of WA Group, Dalforsan remains in front as a trusted global supplier of cladded state-of-the-art rollers. Our rolls can be found in many steel mill applications and the company supplies a tailored package to reduce the cost of repair and increasing productivity with rollers.


See more about Dalforsån visit : www.dalforsan.se



A member of the WA Group since 2011; Produr manufactures a range of advanced ceramic wear & protection materials which are used in a wide range of industrial applications including the steel industry, such as mining and raw material

To find out more about Produr please visit : www.wa-produr.com

Welding Alloys Group is your partner on the whole flowline of steelmaking:



WA Chromecore 400

The ideal solution for your continuous casting rolls.





Through the entire surfacing wires dedicated to the continuous casting rolls, the CHROMECORE 400 family provides excellent resistance to plenty of wear:

- Corrosive environments
- · Elevated temperature
- Cyclic thermal and mechanical stresses
- · High slab contact pressure
- · Adhesive and abrasive wear


High quality cladding technology



Thanks to controlled chemical analysis (%C, %N, etc.), our cladding solution proposed a low delta ferrite contents deposit, improving the corrosion resistance.



Sub arc process



By applying the adequate post weld heat treatment, you will achieve the expected hardness and a high quality deposit.



Thermal cracks to be avoided



Open arc process

WA Chromecore 400


The ideal solution for your continuous casting rolls.




Make the right and appropriate choice

CONTINUOUS CASTING line:

Welding Alloys Group has developed several combinations of cored wires to overlay your low alloys rolls: for Buffer & Final layers





• ROLLING MILL line:

DESCRIPTION	BUFFER LAYER	FINAL LAYERS	HARDNESS
Corrosion	CHROMECORE 430	CHROMECORE 414 COILER	50 HRC
No corrosion	-	HARDFACE DUALHARD C	55 HRC

Reference: Major Steel Manufacturers




WA Corresist

Extend the life of your upper segment rolls.







Welding Alloys Group has become a global specialist in the development of cored wires dedicated to fighting wear.

Through the entire range of surfacing wires dedicated to the continuous casting rolls, the CORRESIST family provides excellent resistance to corrosive environments, high temperature and erosion.

In other words, this family is specially designed for the upper segment rolls of the caster.

The CORRESIST Family is the result of continuous research & development at Welding Alloys. The new wire is an iron-based super alloy and offers outstanding results by performing exceptionally well in high temperatures where corrosion and wear occur.

EN 14700: TFe12

FEATURES

- Open arc / submerged arc and gas shielded wire versions are available
- Iron based super-alloy
- Microstructurally stable at high temperatures
- o Service life comparable to Nickel based alloys

BENEFITS

- High productivity, reduced maintenance costs
- Outstanding oxidation and corrosion resistance
- Improved slab / billet quality
- Less downtime

WA Corresist

Extend the life of your upper segment rolls.



EXTENDED ROLLER LIFETIME





Example: CORRESIST roller lifetime (ø130mm) → 800-1000kT cast steel





REDUCTION IN OFFLINE MAINTENANCE







Weld cladding pioneer!



Your specialized supplier of continuous casting rollers

OUR STRENGTHS

Just in time caster maintenance

A new maintenance concept will reduce maintenance downtime and manpower demands. Replace worn rollers and jackets with new top quality ones, just in time.

First class economy

We offer cladded rollers manufactured to the highest European standards, competitive enough to be compared to Asia's production costs.

Weld surfacing for improved performance

With continuous efforts in productivity and quality, we have been entrusted to supply state of the art rollers worldwide.





PRODUCTS

Rollers

With or without weld cladded surface. Cooled with center bore or revolver bores. Bare rollers or complete assembled with bearings and blocks.

Roller Jackets

Cladded or not to your requirements.

Axles


To complete the supply we are also geared to manufacture the axles.

Roll Assemblies

Together with partners we source bearings etc, to offer you complete assembled roll-lines ready to be installed in the caster segments.













FACILITIES

ROLL CLADDER

Premises

Workshop total area 4000 m2.

Lifting capacity: Overhead cranes up to 30 tons.

Heat treatment furnaces

Electrical convection heated Accuracy at max $950^{\circ}\text{C} = +-5^{\circ}\text{C}$ Workpiece temperature recorded Max. volume: $1600 \times 1600 \times 5300 \text{ mm}$.

Weld surfacing machinery

Automatic welding machine.

For both sub-arc and open-arc welding process depending on customer requirements.

Max. workpiece weight: 30 tons.

Max. workpiece size: Ø 1500 x 6500 mm.

Machining

MACHININ

1 off CNC Lathe Design: PROFILA/NUM, type 1A 670.

Max. workpiece size: Ø 2 100 x 10000 mm.

1 off Horizontal Machining Center Design: HAAS, type EC-1600 YZT.

50-taper geared-head, X=1626, Y=1270, Z=1016 mm.

5 off CNC Lathe Design: D00SAN, type Puma 400.

To mention some of our equipment. The message is that we produce welded rollers in various shapes from bars to finished machined rollers under one roof!

REFERENCES

S E









JSERS





















Galvanising Pots and Rollers





In the metal sheet galvanising process, glavanising pots and rollers are crucial parts subject to high temperature and corrosion. This combination makes the material's selection for wear protection of these parts extremely delicate.

Welding Alloys Group has developed over the last 15 years a specific cladding material and procedure to protect such equipment. For instance, GALVALLOY, a specific cored wire dedicated to resist the galvanising bath environment is designed for corrosion resistance in molten Zn bath. After 2 years in service, material loss is **less than 2 mm!**

- Dedicated to new pots and rolls and for repair & maintenance
 - ▶ Lower investment & maintenance costs, predictable maintenance
- Use of cored wires, Welding Procedures Specification, Automatic Process
 - ► Guaranteed high performance with less downtime
- Crack-free weld deposit
 - ► Guarantee of no localised corrosion in service
- Use of stainless, Ni- and Co-base consumables
 High performance materials achieving maximum lifetime of parts



Galvanising roll after machining

Galvanising Pots and Rollers



Technical Data

- Base material: construction steel P265GH
- Thickness 40 to 100 mm
- 4000mm length, 2500mm width and height
- Up to 20 t weight



Optimised bead surface appearance with GALVALLOY



Galvanising Pot Clad with GALVALLOY



Roller axis after machining



With deposit STELLOY 21-G



Steel Industry GFM Hammers/Forging Saddles





In the forging industry, free forging hammers are a crucial part subject to the heaviest stresses that can be applied to metallic materials. The combination of high temperature, high pressure and metalmetal friction makes the material's selection for wear protection of these parts extremely delicate.

Welding Alloys Group has developed in the last 20 years an expertise in hardfacing free forging hammers, with extensive use of **Stelloy Ni** cored wires. This solution provides extended lifetime and reliability in production.

- Welding procedure developed for multi-layer welding and with different wire sizes
 - No limitation in size
- Use of cored wire
 - ➤ No need for special shielding gases or sophisticated welding equipment meaning a deposition rate up to 10 kgs/hr
- Crack-free weld deposit
 - ► Guarantee of no break-out in service
- Use of Ni-base consumables
 - ► High performance materials achieving maximum lifetime of parts
- Welding procedures for repair of worn hammers or for new hammers
 - ► Cost saving in production



Worn forging saddles

Steel Industry GFM Hammers/Forging Saddles



Our Solutions

Welding Alloys repairs regularly sets of 4 GFM hammers using **Stelloy C + Stelloy Ni 520** in a 2.4mm diameter wire.

The customer requested these have a service life of 200 hours, and previously was only getting 60 hours.

The hammers were sent for machining, flattened and put in service again for a second cycle of 200 hours.



Micrography of a Nickel based superalloys (STELLOY Ni520-G) at 100x magnification



High accuracy in the shape required.



After repair and machining.



Rebuilding of surface in a multi-layer technology.



WA Roll Cladders

Multi*Surfacer*™ Welding Technology The benchmark in roll cladding






The MultiSurfacer™ Roll Cladding machine from Welding Alloys is designed to carry out multi-pass welding of cylindrical components, utilising a range of different welding processes; Open Arc, Submerged Arc and Gas Shielded.

Used globally to weld many different products for the steel industry, the Welding Alloys Roll Cladders typically weld rolls on slab, bloom, billet and thin slab casters as well as hot strip and section mills; improving the roll life and reducing manufacturing & maintenance costs.

Welding Alloys machines enable our customers to fully exploit the benefits of roll reclamation and cladding using Welding Alloys renowned and globally supplied technology.

- · Welding costs are considerably reduced.
- Increased welding capacity.
- Reduction in waste material and associated costs.
- High machinery up time.
- · Intuitive controls increasing productivity.
- 40% reduction in parameter set up time.



Continuous caster roll during submerged arc overlay cladding.

WA Roll Cladders

MultiSurfacer™ Welding Technology The benchmark in roll cladding



Our Solutions

Each roll cladding system can be programmed to accurately weld stringer beads or patterns (spiral, step-over, oscillated & intermittent), cladding/hardfacing with consistently high efficiency and quality.

With multiple machine configurations available, the Multi $Surfacer^{TM}$ Roll Cladding range of machines can be tailored to the customers' requirements, delivering a solution which meets the specifications set by a demanding and varied industry.

Welding Alloys provide the right balance of technology and expertise to each application, ensuring the right product and consumable mix is offered.


For any further information please contact: marketing@welding-alloys.com



Automated flux & slag separation for recirculation.



Rolls clad using WA consumables & roll cladding machines.



Time taken to enter weld parameters during initial set up procedures.



MultiSurfacer™ R3000 Roll Cladder welding a roll with D3-Touch® control technology.



Sinter Stars and Dummy Bars, Crash Decks





In the sintering process, sinter stars, dummy bars and crash decks are crucial parts subject to high temperature, impact and abrasion. This combination makes the material's selection and design for wear protection of these parts extremely delicate.

Welding Alloys Group has developed over the last 20 years an expertise in hardfacing of such equipment, introducing and constantly improving **3-D***Carb*[™] Technology. **3-D***Carb*[™] Technology is exclusively provided by INTEGRA[™].

The interaction of multiple developments result in a massive increase of the lifetime with the longest-running sinter stars having achieved a lifetime of **39 months**.

- Dedicated to new parts and for repair & maintenance
 Higher productivity and lower maintenance costs
- Use of 3-DCarb[™] Technology, optimized design as per analysis of wear phenomena, use of materials resistant to temperature, abrasion and impact
 - ► Improve parts lifetime
- Use of cored wires, Welding Procedures Specification, Automatic Process
 - ► Guaranteed high performance with reduced downtime.
- Use of Cast Steel
 - Easily weldable and re-weldable on site
- Teeth can be replaced separately from the discs



Worn-out sinter stars after 9 months in service

Sinter Stars and Dummy Bars, Crash Decks




Technical Data

Sinter Stars Maximum Diameter:

- 2500mm
- All Dummy Bars Dimensions
- Crash Deck: Thickness up to 150mm



3D-Carb technology



Thermal analysis of parts in service



Sinter Stars repaired before installation





Dummy Bars protected with **3-D***Carb*[™] Technology



Steel Industry Plain Bearings





Grinding of a restored plain bearing

The transport rollers in steel plants are mounted on bearings. These bearings are subject to high temperature stress, abrasion and metal-to-metal friction.

Welding Alloys offers to build up and protect worn bearings using a special antifriction alloy. This involves initial machining, sandblasting, centrifugal coating and machining to the original shape. Ultrasonic and dye penetrant testing ensure the quality of the bearing.

- The lifespan of the part is increased
- · Repair and replacement costs are reduced
- High customer satisfaction
- Reduced downtime



Grinding of a restored plain bearing

Steel Industry Plain Bearings



Our Solution

Bearings in steel plants vary in diameter from 300mm to 1000mm and are subject to heavy abrasion and metal-to-metal friction. Repair and antifriction application with our special soft alloy greatly prolongs the lifetime and reduces the cost of replacing the bearings. Welding Alloys proposes the optimal alloy according to the bearing diameter.



An example of a damaged bearing

Steel Industry Hydraulic Forging Piston





Protection by arc spraying of a hydraulic forging piston

Forging is a manufacturing process involving the shaping of metal using localised compressive forces. High pressure (elastic deformation) and metal abrasion (in the sleeve joint) affect the pistons of the hydraulic press.

Welding Alloys offers an arc spraying solution with a special material to protect them and prolong their lifetime. This material also withstands elastic deformation.

- · Large cost savings through increased lifetime
- · High customer satisfaction
- Reduced downtime



Piston ready for dispatch

Steel Industry Hydraulic Forging Piston



Our Solution

Pistons in forging machinery are subject to high pressure and deformation wear. Welding Alloys provides an arc spraying solution with a special powder which achieves a hardness of 48-51 HRC. The work starts with machining and sandblasting. Several layers are applied by arc spraying.




Diagram of a hydraulic forge



Steel Industry Profiling Mill Rolls





Complete refurbished of a profile mill roll

Profile rolls in steelworks are exposed to heavy abrasive wear and cracking, due to the pressure placed on them when the rolling of billets, bars and rods is in progress.

Horizontial cracks are dangerous and may cause the roll to break, if a crack is left untreated the damage will increase over time. Welding Alloys **Integra**™ has developed a complete repair service which prolongs roll life, giving production of up to 120,000 tonne compared to the original service life of 36,000 tonne. The WA **Integra**™ team uses hardfacing wires to repair any cracks found on the roll.

- · Complete service completed in our workshop
- Tailored wires for surface protection against heat and abrasion
- High customer satisfaction
- · Reduced plant downtime
- · Repair is less costly than purchasing a new part.



Submerged arc welding

Steel Industry Profile Rolls



Our Solution

A typical profile roll can measure 4750mm in length and 850mm in diameter. WA Integra™ will take the roller back to one of our dedicated service centres. Offering a complete repair service, starting with machining of the roll, this removes any rust and material on the roll.

The Integra™ team then carry out non-destructive testing on the roll before cladding with our specially developed submerged arc HARDFACE wire in combination with our WA Flux.

The roll is grinded and finished, before it is delivered back to the mill, ready to go back into production.



Worn out profile rolls



Refurbished profile rolls



Steel Industry Roller Press






Roller press during the arcing process

Roller press mills are used in various industries such as cement, mining and agriculture. In the steel industry these cylindrical rollers are subject to high pressure, impacts and abrasion. The metal forming process causes wear on the rollers as the metal is passed through the rollers.

Welding Alloys offers a cost effective solution to protect the rollers against wear by applying an arc sprayed coating. This solution avoids deformation and allows layers up to 15mm to be deposited.

- · Large cost savings through increased lifetime
- Refurbishment can be carried out in our workshops or in-situ
- High customer satisfaction
- · Reduced mill downtime and increased efficiency



Roller press prepared for arc spraying


Steel Industry Roller Press



Our Solution

Roller presses come in various sizes, for example 3.7m long and 580mm in diameter with a weight of 15.6 tonne – like the roller on the front of this sheet. The base material is often cast iron.

Welding Alloys start by gouging, and dye penetrant testing. This is then followed by rebuilding to the original shape, using arc spraying. The repair can be carried out in our work shop or in-situ depending on the circumstances and customer requirements.



Schema of roller press function



Steel Industry Rolling Mill Bearing (Casing)





Bearing of a rolling mill ready to be dispatched

Most steel mills have a rolling mill division that converts the semi-finished steel products into finished products. This process is done by deformation through compression and reduces the thickness of the steel to get different profiled bars.

The bearings are required to withstand heavy loads and high speed rotations in severe environments. Inside of the casing it must be smooth, rust free and operate under high temperatures, often scratches and wear occur.

- · Machining and buildup to the original shape
- Cost saving, no new parts are needed
- Improvement of durability and service life to withstand heavy loads and high speed rotation
- · High machinery uptime



Bearing during preheating

Steel Industry Rolling Mill Bearing (Casing)



Our Solution

After machining, the part must be cleaned of any lubricant. Inside of the preheated part, a ROBOFIL cored wire is applied, 3mm over the original diameter.

The last step is to machine the inner diameter to the original size.



Back to the original size of the bearing



Close up of bearing







PRODUR UPGRADE FOR WEAR RESISTANCE!

Produr offers advanced solutions for bulk material handling

WA-Produr's wear experts have been working with steel and pyrometallurgy for 25 years and will provide support and advice tailored to the steel industry. Produr uses a wide range of wear resistant materials to protect the processing equipment and to improve reliability, safety and productivity.

OUR STRENGTHS

A wide range of Advanced Wear resistant materials

Durzalt (cast fused Bazalt) Durhart (Cast Fused Alumina) Aldur (Sintered Alumina) SiC (Silicon carbide) Q&T Steels / Hardplates

Engineering capabilities

Produr Engineers analyze your process and requirements and design the adaptive solutions for your equipments

PRODUCTS & SOLUTIONS

Ceramics bucket wheels reclaimers


Ceramic pneumatic conveyors

Ceramics Cyclone / Hydrocyclone

Protection for blast furnaces

Pipping for blast furnaces

Hoppers, chutes, extractors





CERAMIC PIPES



BLAST FURNACE PIPES







FACILITIES

Workshop total area 4'500 sqm Plasma cutting Heavy bending Boiler making Machining Ceramics workshop Lifting capabilities up to 20 tons



REFERENCES















WA Integra ™ Sieves and Screens

Welding Alloys' solution to combat wear in demanding screening applications

In the coke, iron and steelmaking industries, sieves and screens are used in extremely harsh environments that are prone to wear caused by temperature, impact and abrasion. The screening equipment used in these industries are specifically designed to optimise the flow of material and reduce clogging.


The sieves and screens developed by Welding Alloys Group are tailored to our customers' requirements and provide unique solutions in terms of design and diversity of materials used.

Features


- Made of Hardplate
- Conically cut holes
- High flatness
- Complete construction for areas exposed to temperatures up to 700°C
- Holes from min. 4x12mm to open ended in thicknesses from 4mm (2+2) and thicker
- Primary material always in stock

Benefits to You!

- Less clogging
- Minimum 3 x longer lifetime compared to competitors solutions
- Ready to install
- Short delivery times



ASTM G-65 Wear Test (Independent Laboratory)





Waterjet cut holes



Sieve backside



Example of spalling issues (competitor product)



Welding Alloys Sieve after 30 weeks in operation

Competitor Sieve after 16 weeks in operation

Our Technical 'Spark' Solves Your Industrial Challenges




WA Consumables
The go-to provider
of advanced welding
consumables



WA Machines
The go-to provider
of automated equipment
for wear protection



WA Integra[™]
The go-to provider of engineered wear protection solutions



www.welding-alloys.com

